

[illegible]

(43) International Publication Date
29 March 2001 (29.03.2001)

(10) International Publication Number
WO 01/21439 A1

PCT

(51) International Patent Classification⁷: B60R 1/062, (74) Agent: MADDERNS; Level 1, 64 Hindmarsh Square,
F16F 7/10 Adelaide, S.A. 5000 (AU).

(21) International Application Number: PCT/AU00/01163

(81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 25 September 2000 (25.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PQ 3020 23 September 1999 (23.09.1999) AU

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): **BRITAX RAINSFORDS PTY LTD** [AU/AU]; Sheriffs Road, Lonsdale, S.A. 5160 (AU).

Published:


— *With international search report.*

(72) Inventor; and

(75) **Inventor/Applicant (for US only):** GILBERT, Robert, William [AU/AU]; Sherriffs Road, Lonsdale, S.A. 5160 (AU).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VIBRATION SUPPRESSED VEHICLE MIRROR



(57) Abstract: A vehicle external rear vision mirror assembly comprising: a support arm; a mirror frame (14) mounted on an end of the support arm; a support portion (30) connected to the mirror frame (14); a flywheel (34) rotatably mounted with respect to the support portion (30); a means for rotating the flywheel (34); a mirror (40) mounted to the support portion (30), the mirror (40) having a reflective surface orientated substantially normal to the rotational axis of the flywheel (34); and a connection means connecting the support portion (30) to the mirror frame (14), the connection means arranged and constructed such that the angle of the support portion (30), with respect to the mirror frame (14), can be adjusted, whereby the flywheel (34) stabilises the mirror (40) against tilting vibrational movement. The mirror (40) may be mounted either to the support portion (30) (and therefore non-rotatable) or may be mounted directly to the flywheel (34).